



**Manufacturer:**  
AFL

**Product Name:**  
AFL FlowScout® OLS8 FC Adapter Cap

**Manufacturer Part Number:**  
2900-63-0010MR



▶ [Click here for more details on the AFL FlowScout® OLS8 FC Adapter Cap](#)

## FlowScout® OLS8 Optical Light Source

5 YEAR WARRANTY



### Features

- Large color touchscreen with icon-driven user interface
- Rugged, dependable, and backed by industry-best 5-year warranty
- Wave ID generation for reduced test time and user errors
- Field-replaceable connector adapters for maximum flexibility
- AFL's FlexReporter™ Test Results Manager integration (via OPM8)

### Applications

- Enterprise LAN and Data Center fiber networks
- FTTH PON networks
- High power broadband and DWDM systems testing
- Multimode and single-mode fiber networks

AFL's FlowScout OLS8 optical light source represents the next generation of smart optical light sources. Built on the legacy of AFL/Noyes OLS series optical light sources, the FlowScout OLS8 provides a stable and accurate light source for use in enterprise LAN, data center, PON, and broadband networks.

**Intuitive operation:** With a simple-to-use color touchscreen interface, fiber technicians can quickly set-up, test, validate, and document installed fiber plant, as well as perform troubleshooting as needed.

**Wave ID for reduced test time and errors:** In the Wave ID mode, the OLS8 encodes each wavelength with a unique Wave ID code. When used with a Wave ID capable power meter, such as OPM8, the pair can test up to three wavelengths simultaneously reducing test time and eliminating wavelength-setting errors. The light source also offers CW mode (continuous output - no encoding) and supports test Tone generation (270 Hz, 330 Hz, 1 kHz, 2 kHz) to assist in troubleshooting.

**Flexible reporting:** When used in conjunction with AFL's FlowScout OPM8 power meter, test results may be transferred to a PC running FlexReports PC software. Illuminate your network and report in real-time using AFL's FlowScout OLS8!

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*








**Manufacturer:**  
AFL  
**Product Name:**  
AFL FlowScout® OLS8 FC Adapter Cap  
**Manufacturer Part Number:**  
2900-63-0010MR

▶ Click here for more details on the AFL FlowScout® OLS8 FC Adapter Cap

## FlowScout® OLS8 Optical Light Source

### Product Highlights


-  **Icon-driven Interface**
-  **Comprehensive Reporting (With OPM)**
-  **Handheld**
-  **Battery Operated**
-  **USB Power Port / Software Upgrades**

**Field-replaceable output adapter**  
Field-replaceable output adapters enable access for inspection and cleaning of optical ports and supports multiple connector styles.


**Large color display**  
Large color touchscreen, visible in direct sunlight, displays a simple to use user interface.

**Clear test parameter setup**  
Intuitive, quick, and simple set-up for seamless testing, validation, and reporting.


**Durable design for field use**  
Rugged design backed by industry-best 5-year warranty.




### User Interface Highlights




Clear Home Screen




Select Source Mode



Select Wavelength



General Settings




Test Results Transfer to FlexReports PC Software

Contact the professionals at Fiber Optic Center for a quote or to get more details.

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.



**Manufacturer:**  
AFL

**Product Name:**  
AFL FlowScout® OLS8 FC Adapter Cap

**Manufacturer Part Number:**  
2900-63-0010MR

▶ [Click here for more details on the AFL FlowScout® OLS8 FC Adapter Cap](#)

## FlowScout® OLS8 Optical Light Source

### Specifications <sup>(a)</sup>, <sup>(b)</sup>

Optical									
Model	OLS8-QUAD (MM Optical Port)		OLS8-QUAD (SM Optical Port)		OLS8-SM (Single Port)		OLS8-XGS (Single Port)		
Wavelength	850 ±30 nm	1300 ±20 nm	1310 ±20 nm	1550 ±20 nm	1310 ±20 nm	1550 ±20 nm	1310 ±20 nm	1550 ±20 nm	1490 ±20 nm
Spectral Width	45 nm (typ.)	120 nm (typ.)	5 nm (max)						
Emitter Type	LED			Laser					
Safety Class	Class I FDA 21 CFR 1040.10 and 1040.11, IEC 60825-1: 2007-03								
Output Power	>-20 dBm, 50 µm multimode			-1 dBm, 9 µm single-mode					
Output Stability	±0.1 dB over 8 hours (after 5 minutes warm-up)			±0.05 dB over 1 hour (after 15 minutes warm-up) ±0.1 dB over 8 hours (after 15 minutes warm-up)					
Tone Output	270 Hz, 330 Hz, 1 kHz, 2 kHz								
Wave ID	Automatically detects and measures power & loss at one or more wavelengths using any AFL Wave ID source								
General									
Available Adapters	SC FC, ST, LC								
Power	120/240 VAC input; 5VDC @2A output to USB-C								
Battery	User replaceable Li-Pol; IEC 62133-2:2017 and UN38.3 certified								
Operating Time (typical) <sup>(d)</sup>	10 hours continuous use								
Recharge Time <sup>(d)</sup>	≤3 hours								
Data Interfaces	USB-C								
Operating Temperature	-10 °C to +50 °C, 95% RH (non-condensing)								
Storage Temperature	-30 °C to +60 °C, 95% RH (non-condensing)								
IP Rating	IP54								
Shock & Vibration	Withstands 1 m drop test on all 6 sides								
Data Storage	Non-volatile memory for field-updateable software and results storage								
Display	3.5 in. color backlit LCD; capacitive touchscreen; 320 X 480 pixels								
Size (H x W x D)	14.0 x 8.1 x 3.3 cm (5.5 x 3.2 x 1.3 in)								
Weight	≤290 g (≤0.65 lb)								
Calibration	N.I.S.T. traceable; ≥ 3 years between required re-calibration								
Warranty	5 years								

### Notes:

- a. All specifications valid at 25°C unless otherwise specified.
- b. All OLS models are equipped with SC/UPC port as standard.
- c. Operating conditions: 60 tests in 20 minutes, then auto-off; repeat each hour. Display backlight at minimum brightness.
- d. Charging time data is provided for USB-C 2A charger supported Power Delivery 3.0.

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*



**Manufacturer:**  
AFL

**Product Name:**  
AFL FlowScout® OLS8 FC Adapter Cap

**Manufacturer Part Number:**  
2900-63-0010MR

▶ [Click here for more details on the AFL FlowScout® OLS8 FC Adapter Cap](#)

## FlowScout® OLS8 Optical Light Source

### Ordering Information

AFL NO.	Emitter Type	Output Ports	Output Wavelengths (nm)				
			850	1300	1310	1490	1550
OLS8-SM DUAL	Laser	1			◆		◆
OLS8-QUAD	LED + Laser	2	◆	◆	◆		◆
OLS8-SM XGS	Laser	1			◆	◆	◆


All OLS8 models include protective rubber boot, SC/UPC adapter, rechargeable Li-Pol battery, carry case and data + power cord. Test jumpers and connector adapters are required for operation (purchased separately). Test jumpers with a variety of connector styles and fiber types and adapter caps for most common connectors may be purchased from AFL.

AFL NO.	Description
OLS8-SL2-0001MR	<b>FlowScout OLS8-SM DUAL (1310/1550 nm) Basic Kit.</b> Includes: FlowScout OLS8-SM DUAL light source, AC charger and power cable, quick reference guide, and soft carry case.
OLS8-SL4-0001MR	<b>FlowScout OLS8-QUAD (850/1300/1310/1550 nm) Basic Kit.</b> Includes: FlowScout OLS8-QUAD light source, AC charger and power cable, quick reference guide, and soft carry case.
OLS8-SL7-0001MR	<b>FlowScout OLS8-SM XGS (1310/1490/1550 nm) Basic Kit.</b> Includes FlowScout OLS8-SM XGS light source, AC charger and power cable, quick reference guide, and soft carry case.

### Connector Adapters


AFL NO.	Description
2900-63-0007MR	SC/UPC Adapter for FlowScout OLS8
2900-63-0008MR	LC/UPC Adapter for FlowScout OLS8
2900-63-0009MR	ST/UPC Adapter for FlowScout OLS8
2900-63-0010MR	FC/UPC Adapter for FlowScout OLS8

### Recommended Products



**FlowScout OPM8 Optical Power Meter**

- Rapid pass/fail analysis based on user-set limits
- Wave ID functionality for accuracy and reduced test time
- Internal test results storage
- Test results transfer via USB, Bluetooth, and free FlexApp
- Reports generation using AFL's FlexReporter™



**OFI-BIPM Optical Fiber Identifier**


- World-class signal sensitivity
- Trigger lock, positive stop for optimum detection
- Integrated optical power meter option

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*



Manufacturer: AFL
Product Name: AFL FlowScout® OLS8 FC Adapter Cap
Manufacturer Part Number: 2900-63-0010MR

Click here for more details on the AFL FlowScout® OLS8 FC Adapter Cap

FlowScout® OLS8 Optical Light Source

Qualifications

Table with 3 columns: Category, Regulation/Standard, Qualification. Rows include CE Marking, UKCA Marking, Safety/EMC/EMI, RoHS, Test Method, and Generic Requirement.

\* A complementary encircled flux mode conditioner may be needed to comply with encircled flux launch conditions for testing multimode optical fiber cabling and components.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.