

### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)



### **EPO-TEK® 301-2 PART B**

Safety Data Sheet

A Meridian Adhesives Group Company

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/18/2022 Revision date: 5/24/2023 Supersedes: 5/18/2022 Version: 2.0

#### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture

: EPO-TEK® 301-2 PART B Product name

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives Recommended use : Adhesives

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

#### Manufacturer

Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA 01821 USA

T 978-667-3805 - F 978-663-9782

www.epotek.com

#### 1.4. Emergency telephone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

#### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### GHS US classification

H314 Skin corrosion/irritation Category 1C Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Hazardous to the aquatic environment - Chronic Hazard Category 3 H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

Hazard pictograms (GHS US)

: Danger

Signal word (GHS US)

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H412 - Harmful to aquatic life with long lasting effects Precautionary statements (GHS US) : P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

## **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulation

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

#### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name		Product identifier	%	GHS US classification
Polyoxypro	pylenediamine	CAS-No.: 9046-10-0	≥ 60	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412

Comments

: \*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Components not listed are either non-hazardous or are below reportable limits.

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do Continue rinsing Call a physician immediately

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact · Burns

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

## **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapors/spray.

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

#### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### EPO-TEK® 301-2 PART B

No additional information available

Polyoxypropylenediamine (9046-10-0)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Color Odor slight Odor threshold No data available : No data available Melting point No data available Freezing point No data available **Boiling point** No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available : Not applicable. : No data available Vapor pressure Relative vapor density at 20°C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature

Data is subject to change without notice.

Decomposition temperature





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

#### **EPO-TEK® 301-2 PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

### 9.2. Other information

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

# 11.1. Information on toxicological effects Acute toxicity (oral)

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

## Polyoxypropylenediamine (9046-10-0)

Polyoxypropylenediamine (9046-10-0)	
LD50 oral rat	2885 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	2980 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 0.74 mg/l air (Equivalent or similar to OECD 403, 8 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	2885 mg/kg body weight
ATE US (dermal)	2980 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Data is subject to change without notice.





## **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

### SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Polyoxypropylenediamine (9046-10-0)	
LC50 - Fish [1]	772.14 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinodon variegatus, Static system, Salt water, Experimental value, GLP)
EC50 - Crustacea [1]	80 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	15 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

### 12.2. Persistence and degradability

Polyoxypropylenediamine (9046-10-0)	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

Polyoxypropylenediamine (9046-10-0)	
Partition coefficient n-octanol/water (Log Pow)	1.34 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

Polyoxypropylenediamine (9046-10-0)	
Surface tension	Data waiving
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

No additional information available

#### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

 $Data\ is\ subject\ to\ change\ without\ notice.$ 





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No : UN2735 UN-No. (TDG) : UN2735 UN-No. (IMDG) : 2735 UN-No. (IATA) : 2735

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)
Proper Shipping Name (TDG) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine)
Proper Shipping Name (IMDG) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine)
Proper Shipping Name (IATA) : Amines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)

#### 14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Hazard labels (DOT) :



TDG

Transport hazard class(es) (TDG) : Hazard labels (TDG) :



IMDG

Transport hazard class(es) (IMDG) : Hazard labels (IMDG) :



IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



## 14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III
Packing group (IMDG) : III

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulati

Packing group (IATA) : 111

#### 14.5. Environmental hazards

Other information : No supplementary information available

### 14.6. Special precautions for user

UN-No.(DOT)

DOT Special Provisions (49 CFR 172.102)

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 203 DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) 241 DOT Quantity Limitations Passenger aircraft/rail (49 : CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 · 60 I

CFR 175.75)

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

UN-No. (TDG) TDG Special Provisions UN2735

MAWP.

: 16 - (1) The technical name of at least one of the most dangerous substances that predom contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the

disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S:

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S, or ALKALOIDS, LIQUID, N.O.S;

(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or

(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.

Explosive Limit and Limited Quantity Index Excepted quantities (TDG)

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number

Data is subject to change without notice.

## Contact the professionals at Fiber Optic Center for a quote or to get more details.

5 L

E1

: 5 L





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### IMDG

 Special provision (IMDG)
 : 223, 274

 Limited quantities (IMDG)
 : 5 L

 Excepted quantities (IMDG)
 : E1

 Packing instructions (IMDG)
 : P001, LP01

 IBC packing instructions (IMDG)
 : IBC03

 Tank instructions (IMDG)
 : T7

 Tank special provisions (IMDG)
 : TP1, TP28

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : A

Properties and observations (IMDG)

: Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y841 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 852 : 5L PCA max net quantity (IATA) CAO packing instructions (IATA) : 856 CAO max net quantity (IATA) : 60L Special provision (IATA) : A3, A803 ERG code (IATA) : 8L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

CANADA

#### Polyoxypropylenediamine (9046-10-0)

Listed on the Canadian DSL (Domestic Substances List)

### **EU-Regulations**

No additional information available

National regulations

### Polyoxypropylenediamine (9046-10-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Data is subject to change without notice.





Manufacturer:

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

## **Manufacturer Part Number:**

ET301-2-2.5G

Click here for more details on the EPO-TEK® 301-2 Transparent Epoxy, Room Temperature Cure (2.5g)

### **EPO-TEK® 301-2 PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 05/24/2023

Full text of H-phrases		
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H412	Harmful to aquatic life with long lasting effects	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

 $Data\ is\ subject\ to\ change\ without\ notice.$ 

