

### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019 Revision: 2 Supersedes date: 9/5/2014



# SAFETY DATA SHEET EPO-TEK® 305 Part A

1. Identification

Product identifier

Product name EPO-TEK® 305 Part A

Product number 305/A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821 USA (978) 667-3805

(978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

Environmental hazards Not Classified

Label elements
Hazard symbols



Signal word Warning

Hazard statements H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.







### Manufacturer:

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019	Revision: 2 Supersedes date: 9/5/2014			
	EPO-TEK® 305 Part A			
3. Composition/information on ingredients				
Mixtures				
Substituted Glycidyl Ether Re CAS number: Proprietary	esin 60-100%			
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319				
The full text for all hazard stat	ements is displayed in Section 16.			
Ingredient notes	The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200. The exact identity is withheld as a trade secret in accordance with 29 CFR 1910.1200.			
4. First-aid measures				
Description of first aid measur	es			
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.			
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.			
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.			
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.			
Most important symptoms and	effects, both acute and delayed			
Inhalation	Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.			
Ingestion	May cause discomfort if swallowed.			
Skin contact	Causes skin irritation.			
Eye contact	May cause severe eye irritation.			
Indication of immediate medic	al attention and special treatment needed			
Notes for the doctor	Treat symptomatically.			
5. Fire-fighting measures				
Extinguishing media				
Suitable extinguishing media	Extinguish with the following media: Dry chemicals. Foam. Water spray.			
Special hazards arising from t	he substance or mixture			
Hazardous combustion products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.			
Advice for firefighters				
Protective actions during firefighting	Avoid breathing fire gases or vapors.			





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET305-4G

Supersedes date: 9/5/2014 Revision date: 10/9/2019

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4q)

#### EPO-TEK® 305 Part A

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective for firefighters

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

**Environmental precautions** 

**Environmental precautions** Avoid release to the environment.

#### Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

#### 7. Handling and storage

#### Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and

contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety

data sheet.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash contaminated skin thoroughly after handling. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent

drying of skin.

#### Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

### 8. Exposure controls/Personal protection

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls





Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eve/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Data is subject to change without notice.

### Contact the professionals at Fiber Optic Center for a quote or to get more details.





### Manufacturer:

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019	Revision: 2 Supersedes date: 9/5/	/201	
	EPO-TEK® 305 Part A		
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.		
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.		
9. Physical and chemical prop	perties		
Information on basic physical	and chemical properties		
Appearance	Liquid.		
Color	Clear liquid.		
Odor	Mild.		
Odor threshold	No specific test data are available.		
pH	No specific test data are available.		
Melting point	No specific test data are available.		
Initial boiling point and range	No specific test data are available.		
Flash point	118°C		
Evaporation rate	< BuAc		
Flammability (solid, gas)	No specific test data are available.		
Upper/lower flammability or explosive limits	No specific test data are available.		
Vapor pressure	No specific test data are available.		
Vapor density	>1		
Relative density	No specific test data are available.		
Bulk density	«59» «184» «109012»		
Solubility(ies)	Slightly soluble in water.		
Partition coefficient	No specific test data are available.		
Auto-ignition temperature	No specific test data are available.		
Decomposition Temperature	No specific test data are available.		
Viscosity	No specific test data are available.		
Other information	None.		
10. Stability and reactivity			
Reactivity	The following materials may react with the product: Acids. Strong alkalis. Strong oxidizing agents. Strong reducing agents.		
Stability	Stable at normal ambient temperatures and when used as recommended.		
Possibility of hazardous reactions	Will not polymerize.		
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources ignition.	0	







### Manufacturer:

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019	Revision: 2	Supersedes date: 9/5/2014			
	EPO-TEK® 305 Part A				
Materials to avoid	Strong acids. Strong alkalis. Strong oxidizing agents. Strong reducing agents.				
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.				
11. Toxicological information					
Information on toxicological effects					
Inhalation	Gas or vapor in high concentrations may irritate the respiratory system during cutting, grinding or sanding operations involving this product in respiratory tract.				
Ingestion	May cause discomfort if swallowed.				
Skin Contact	Irritating to skin.				
Eye contact	Causes serious eye irritation.				
12. Ecological information					
Acute aquatic toxicity					
Acute toxicity - fish	No information available.				
Persistence and degradability					
Persistence and degradability	The product is moderately biodegradable.				
Bioaccumulative potential					
Bio-Accumulative Potential	The product contains potentially bioaccumulating substances.				
Partition coefficient	No specific test data are available.				
Mobility in soil					
Mobility	Mobile.				
Other adverse effects					
Other adverse effects	Not known.				
13. Disposal considerations					
Waste treatment methods Disposal methods	Dispose of waste to licensed waste disposal site in accordance with t local Waste Disposal Authority.	he requirements of the			
14. Transport information					
General	The product is not covered by international regulations on the transport (IMDG, IATA, DOT).	ort of dangerous goods			
UN Number					
UN No. (International)	Not applicable.				
UN No. (DOT)	Not applicable.				
UN proper shipping name					
Proper shipping name (International)	Not applicable.				
Proper shipping name (DOT)	Not applicable.				





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019 Revision: 2 Supersedes date: 9/5/2014

#### EPO-TEK® 305 Part A

Transport hazard class(es)

Transport Labels (International)

No transport warning sign required.

**DOT transport labels** 

No transport warning sign required.

Packing group

Packing group (International) Not applicable.

DOT packing group Not applicable.

**Environmental hazards** 

**Environmentally Hazardous Substance** 

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Not applicable Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Regulatory References

Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of

Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

None of the ingredients are listed.

CAA Accidental Release Prevention None of the ingredients are listed.

.....

OSHA Highly Hazardous Chemicals None of the ingredients are listed.

**US State Regulations** 

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed.







### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4q)

Revision date: 10/9/2019 Revision: 2 Supersedes date: 9/5/2014 EPO-TEK® 305 Part A California Air Toxics "Hot Spots" (A-II) None of the ingredients are listed. Massachusetts "Right To Know" List None of the ingredients are listed. Rhode Island "Right To Know" List None of the ingredients are listed. Minnesota "Right To Know" List None of the ingredients are listed. New Jersey "Right To Know" List None of the ingredients are listed. Pennsylvania "Right To Know" List None of the ingredients are listed. Inventories EU - EINECS/ELINCS None of the ingredients are listed. Canada - DSL/NDSL All the ingredients are listed or exempt. US - TSCA All the ingredients are listed or exempt. US - TSCA 12(b) Export Notification None of the ingredients are listed. Australia - AICS All the ingredients are listed or exempt. Japan - ENCS None of the ingredients are listed. Korea - KECI All the ingredients are listed or exempt. China - IECSC All the ingredients are listed or exempt. Philippines - PICCS None of the ingredients are listed. 16. Other information Revision date 10/9/2019 Revision Supersedes date 9/5/2014 Hazard statements in full H315 Causes skin irritation.

Data is subject to change without notice.



H319 Causes serious eve irritation.



**Manufacturer:** Epoxy Technology

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

**Manufacturer Part Number:** 

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019 Revision: 2 Supersedes date: 9/5/2014

EPO-TEK® 305 Part A

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



