

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)



EPO-TEK® 383ND PART B

Safety Data Sheet

A Meridian Adhesives Group Company

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 8/28/2023 Revision date: 10/26/2023 Supersedes: 8/28/2023 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : EPO-TEK® 383ND PART B

1.2. Recommended use and restrictions on use

Recommended use : Adhesives
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Supplier

Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
T 978-667-3805 - F 978-663-9782
www.epotek.com

1.4. Emergency telephone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

| | | |
|--|------|---|
| Acute toxicity (oral) Category 4 | H302 | Harmful if swallowed |
| Skin corrosion/irritation Category 1B | H314 | Causes severe skin burns and eye damage |
| Serious eye damage/eye irritation Category 1 | H318 | Causes serious eye damage |
| Skin sensitization, Category 1 | H317 | May cause an allergic skin reaction |
| Carcinogenicity Category 2 | H351 | Suspected of causing cancer |

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H351 - Suspected of causing cancer

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|------------------------|-----------------------|---------|--|
| Substituted imidazole* | CAS-No.: Trade Secret | 30 – 60 | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 |
| Substituted imidazole* | CAS-No.: Trade Secret | < 30 | Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 |
| Substituted imidazole* | CAS-No.: Trade Secret | 5 – 10 | Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Carc. 2, H351 |
| Substituted anhydride* | CAS-No.: Trade Secret | < 5 | Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments

: Components not listed are either non-hazardous or are below reportable limits.

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Call a physician immediately. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. |
| First-aid measures after ingestion | : Rinse mouth. Do not induce vomiting. Call a physician immediately. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|---|
| Symptoms/effects after skin contact | : Burns. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : Burns. |

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. For more storage information please refer to the Technical Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EPO-TEK® 383ND PART B

No additional information available

Substituted anhydride

No additional information available

Substituted imidazole

No additional information available

Substituted imidazole

No additional information available

Substituted imidazole

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| |
|--|
| Skin and body protection: |
| Wear suitable protective clothing |
| Respiratory protection: |
| In case of insufficient ventilation, wear suitable respiratory equipment |

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------|
| Physical state | : Liquid |
| Color | : Clear |
| Odor | : slight |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20°C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| EPO-TEK® 383ND PART B | |
|---------------------------|--|
| ATE US (oral) | 352.869 mg/kg body weight |
| Substituted anhydride | |
| LD50 oral rat | ≈ 1144 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other: |
| LD50 dermal rabbit | 400 – 640 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| ATE US (oral) | 500 mg/kg body weight |
| ATE US (dermal) | 400 mg/kg body weight |
| Substituted imidazole | |
| LD50 oral rat | 350 mg/kg Source: IUCLID |
| LD50 oral | 173 mg/kg |
| LD50 dermal rabbit | 440 mg/kg Source: IUCLID |
| ATE US (oral) | 173 mg/kg body weight |
| ATE US (dermal) | 440 mg/kg body weight |
| Substituted imidazole | |
| LD50 oral rat | 731 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral) |
| LD50 dermal rabbit | > 400 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal) |
| LC50 Inhalation - Rat | > 0.03 mg/l (Equivalent or similar to OECD 403, 8 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours)) |
| ATE US (oral) | 731 mg/kg body weight |
| Substituted imidazole | |
| ATE US (oral) | 100 mg/kg body weight |
| Skin corrosion/irritation | : Causes severe skin burns. |
| Substituted anhydride | |
| pH | 11.3 (10 %) |

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-------------------------------------|---|
| Substituted imidazole | |
| pH | 10.6 (10 %) |
| Substituted imidazole | |
| pH | 10.9 (21 %) |
| Serious eye damage/irritation | : Causes serious eye damage. |
| Substituted anhydride | |
| pH | 11.3 (10 %) |
| Substituted imidazole | |
| pH | 10.6 (10 %) |
| Substituted imidazole | |
| pH | 10.9 (21 %) |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Suspected of causing cancer. |
| Substituted imidazole | |
| IARC group | 2B - Possibly carcinogenic to humans |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |
| Substituted imidazole | |
| STOT-single exposure | May cause respiratory irritation. |
| STOT-repeated exposure | : Not classified |
| Substituted anhydride | |
| NOAEL (oral,rat,90 days) | 90 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents) |
| Substituted imidazole | |
| NOAEL (oral,rat,90 days) | 150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA OPPTS 870.3650 (Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test) |
| Aspiration hazard | : Not classified |
| Viscosity, kinematic | : No data available |
| Substituted imidazole | |
| Viscosity, kinematic | 1435.897 mm ² /s |
| Symptoms/effects after skin contact | : Burns. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : Burns. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Substituted anhydride | |
|---|--|
| LC50 - Fish [1] | 100 – 215 mg/l Test organisms (species): Leuciscus idus |
| EC50 - Crustacea [1] | 267.94 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | 180 mg/l (Algae) |
| EC50 96h - Algae [1] | 12.637 mg/l Source: Ecological Structure Activity Relationships |
| Substituted imidazole | |
| LC50 - Fish [1] | 0.34 mg/l Source: IUCLID |
| EC50 - Crustacea [1] | 180 mg/l Source: IUCLID |
| EC50 72h - Algae [1] | 2 mg/l Source: IUCLID |
| Substituted imidazole | |
| LC50 - Fish [1] | 68.1 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value) |
| EC50 - Crustacea [1] | 297.3 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| EC50 72h - Algae [1] | 124.8 mg/l (DIN 38412-9, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Growth rate) |
| EC50 72h - Algae [2] | 72 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| EC50 96h - Algae [1] | 6.057 mg/l Source: Ecological Structure Activity Relationships |
| 12.2. Persistence and degradability | |
| Substituted anhydride | |
| Not rapidly degradable | |
| Persistence and degradability | Not readily biodegradable in water. |
| Substituted imidazole | |
| Not rapidly degradable | |
| Persistence and degradability | Inherently biodegradable. |
| Biochemical oxygen demand (BOD) | 0.000002 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 0.0015 g O ₂ /g substance |
| Substituted imidazole | |
| Not rapidly degradable | |
| Persistence and degradability | Readily biodegradable in water. |
| Substituted imidazole | |
| Not rapidly degradable | |
| 12.3. Bioaccumulative potential | |
| Substituted anhydride | |
| Partition coefficient n-octanol/water (Log Pow) | -0.06 Source: ChemIDplus |


Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Substituted imidazole | |
|--|---|
| Partition coefficient n-octanol/water (Log Pow) | 0.35 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| Substituted imidazole | |
| Partition coefficient n-octanol/water (Log Pow) | 1.13 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| 12.4. Mobility in soil | |
| Substituted anhydride | |
| Mobility in soil | 15.75 Source: Quantitative Structure Activity Relation |
| Substituted imidazole | |
| Mobility in soil | 28.23 Source: EPI SUITE |
| Ecology - soil | No (test)data on mobility of the substance available. |
| Substituted imidazole | |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 3.71 (log Koc, Calculated value, pH = 7) |
| Ecology - soil | Low potential for mobility in soil. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No : UN3267
UN-No. (TDG) : UN3267
UN-No. (IMDG) : 3267
UN-No. (IATA) : 3267

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s. (Substituted imidazole)
Proper Shipping Name (TDG) : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Substituted imidazole)
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Substituted imidazole)
Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s. (Substituted imidazole)

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : 8
Hazard labels (TDG) : 8



IMDG

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3267

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|--|
| DOT Special Provisions (49 CFR 172.102) | : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 154 |
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 202 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 242 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 1 L |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 30 L |
| DOT Vessel Stowage Location | : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. |
| DOT Vessel Stowage Other | : 40 - Stow "clear of living quarters"; 52 - Stow "separated from" acids |
| TDG | |
| UN-No. (TDG) | : UN3267 |
| TDG Special Provisions | : 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. |
| Explosive Limit and Limited Quantity Index | : 1 L |
| Excepted quantities (TDG) | : E2 |
| Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index | : 1 L |
| Emergency Response Guide (ERG) Number | : 153 |

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

| | |
|------------------------------------|---|
| Special provision (IMDG) | : 274 |
| Limited quantities (IMDG) | : 1 L |
| Excepted quantities (IMDG) | : E2 |
| Packing instructions (IMDG) | : P001 |
| IBC packing instructions (IMDG) | : IBC02 |
| Tank instructions (IMDG) | : T11 |
| Tank special provisions (IMDG) | : TP2, TP27 |
| EmS-No. (Fire) | : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE |
| EmS-No. (Spillage) | : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES |
| Stowage category (IMDG) | : B |
| Stowage and handling (IMDG) | : SW2 |
| Segregation (IMDG) | : SGG18, SG35 |
| Properties and observations (IMDG) | : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes. |

IATA

| | |
|--|------------|
| PCA Excepted quantities (IATA) | : E2 |
| PCA Limited quantities (IATA) | : Y840 |
| PCA limited quantity max net quantity (IATA) | : 0.5L |
| PCA packing instructions (IATA) | : 851 |
| PCA max net quantity (IATA) | : 1L |
| CAO packing instructions (IATA) | : 855 |
| CAO max net quantity (IATA) | : 30L |
| Special provision (IATA) | : A3, A803 |
| ERG code (IATA) | : 8L |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Substituted anhydride

Listed on the Canadian DSL (Domestic Substances List)

Substituted imidazole

Listed on the Canadian NDSL (Non-Domestic Substances List)

Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Data is subject to change without notice.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 383ND High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:
ET383ND-8OZ

▶ [Click here for more details on the EPO-TEK® 383ND High Temperature Epoxy, Heat Cure \(8oz\)](#)

EPO-TEK® 383ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Substituted anhydride

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Substituted imidazole

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

WARNING: This product can expose you to Substituted imidazole, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 10/26/2023

| Full text of H-phrases | |
|------------------------|---|
| H301 | Toxic if swallowed |
| H302 | Harmful if swallowed |
| H311 | Toxic in contact with skin |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H335 | May cause respiratory irritation |
| H351 | Suspected of causing cancer |

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com

