



Manufacturer:
Seikoh Giken

Product Name:
Seikoh Giken Pre-Radius 4 Slot Zirconia 2.5mm Ferrule 125um


Manufacturer Part Number:
SZ-3A1412580G

>> Find Out More Details on the Seikoh Giken Pre-Radius 4 Slot Zirconia 2.5mm Ferrule 125um <<

Product Data Sheet

Page 1 of 1

SZ-3A 2.5mm Single Mode Pre-dome Endface Zirconia Ferrule



Features & Benefits

- Realization of excellent wear and shock resistance, high-durability against repeated insertion, removal and highly reliable connections.
- Wide product lineup, including 2.5, 125, pred-dome, Angle PC and funnel shape types, makes it possible to respond to a diverse range of user needs.
- Reduced assembly time.
- High-quality of end face radius.



Specifications

End Face Radius	15 = 3/-5mm
Outside Diameter & Tolerance	2499.0 ± 0.5
Hole Eccentricity	0.7 or less (0.5 is available)
Hole Diameter Tolerance	+ 1.0/-0
Hole Diameter	S5 S5.5 S6
Hole Diameter(um)	125um 125.5um 126um

Ordering Information

Model Number	Type Number						
SZ-3A	1	4	1	2	5	0	0
Ferrule O.D. (mm)	(Required)						
1 : ø 2.5							
Flange							
4 : 4-slots							
Ferrule I.D. (µm)	Detail Specification						
ø 125 ø 125.5(12F) ø 126	0 : SII standard Eccentricity = 0.7 micron or less						
	8 : Eccentricity = 0.5 micron or less						

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.