



**Manufacturer:** 

VIAVI

**Product Name:** 

Single 1X8 SMF Bulkhead FC/APC Without Option

Manufacturer Part Number: MOSW-C111C008B0-M100-MFA-MO

Click here for more details on the Single 1X8 SMF Bulkhead FC/APC Without Option

Data Sheet

### **VIAVI**

# **Optical Switch Module (mOSW-C1)**

**Optical Switch for MAP Series** 

The mOSW-C1 Optical Switch module is the industry standard for manufacturing test automation applications and has the widest range of switch options in the industry. A member of the LightDirect Family of MAP series modules, the mOSW-C1 can be deployed in the compact MAP-220C 2-slot chassis or the larger 3 and 8 slot chassis systems (second generation MAP-230B & MAP-280 or the third generation MAP-330 & MAP-380).



### **Configuration Process**

All mOSW switches are configured by a single part number that completely defines the function and options of the switch.

The structure of the part number mOSW-C1ABBCCCDE-MXXX-MYY is as follows:

- ${\bf A}$  refers to the number of independent mOSW-C1 switches in the module (1, 2, or 4)
- BB refers to the switch type and defines the input type (1C, 2D¹, 2E, 2X)
- **CCC** defines the number of outputs (from 002 to 064, increments shown in table)
- $\boldsymbol{\mathsf{D}}$  defines the termination type (B for bulkhead, P for 2m pigtails)
- ${\bf E}$  defines the options (0 = no option, 1 = Power Trim option<sup>2</sup>, H = High Directivity<sup>3</sup>)

MIC

MIU

 $M\boldsymbol{XXX}$  defines the fiber type, refer to Table 1

MYY defines the connector type, refer to Table 2

Table 1	
Code	Fibre Type
M100	9µm Single Mode
M101	50μm (OM3)
M102	62.5µm (OM1)
M105 <sup>4</sup>	100µm

Table 2		
Code	Connector Type	
MFP	FC/PC	
MFA	FC/APC	
MSC	SC/PC	
MSU	SC/APC	

LC/PC

LC/APC

#### Notes

- D Config part numbers indicate the number of switchable output states. The total number of physical output connectors will be 2X the number of states i.e. 2Dx004 has 8 output connectors
- Power Trim option is available only for 1C type switch with 9µm Single Mode fiber with the exception of switch type 1c002
- 3. High Directivity option is available only for 1C002 & 2X002 type switch with 9µm Single Mode fiber
- 4. 100µm fiber type is available only for Bulkhead termination



Single-width module



Double-width module

# Contact the professionals at Fiber Optic Center for a quote or to get more details.